

TECHNI CONNECT 28

Operating Temperature Range:

- 30 / + 400 C°

Features:

- Very high temperature resistance
- Suitable for health applications
- Good compressibility: to 1:7 ratio
- External galvanised steel helix protects against abrasion
- Silicone free
- Improved vacuum resistance - woven in reinforcement

For use in:

- Hot air transfer
- Defence industries
- Exhaust transfer
- Low pressure applications
- Glass factory
- Furnace construction
- Iron and steel industries
- Moulding applications

Lengths (on application):

127 mm – 457 mm ID – 10-20 metres

508 mm – 1240 mm ID – 5-10 metres



PART CODES: PRICES & TECHNICAL SPECIFICATIONS

PRODUCT CODE	INNER DIAMETER	WORKING PRESSURE	VACUUM	BENDING RADIUS	WEIGHT
	<i>mm</i>	<i>bar</i>	<i>bar</i>	<i>mm</i>	<i>gr./mt.</i>
28-01-127	127	0,180	0,048	99,0	1,115
28-01-133	133	0,157	0,045	103,0	1,140
28-01-140	140	0,115	0,039	110,5	1,190
28-01-152	152	0,107	0,036	101,5	1,05
28-01-160	160	0,105	0,031	108,0	1,085
28-01-180	180	0,085	0,028	121,0	1,250
28-01-203	203	0,080	0,024	134,0	1,410
28-01-229	229	0,072	0,020	162,0	1,640
28-01-254	254	0,049	0,015	179,0	1,825
28-01-280	280	0,039	0,013	197,0	2,105
28-01-305	305	0,032	0,011	214,0	2,285
28-01-315	315	0,028	0,010	224,5	2,315
28-01-356	356	0,20	0,008	249,0	2,695
28-01-406	406	0,018	0,005	284,0	3,255
28-01-457	457	0,012	0,004	341,5	3,715
28-01-508	508	0,010	0,004	379,0	4,175
28-01-559	559	0,008	0,003	436,0	4,685
28-01-610	610	0,007	0,003	454,0	5,145
28-01-710	710	0,005	0,002	529,0	6,020
28-01-820	820	0,003	0,002	604,0	6,890
28-01-920	920	0,002	0,002	679,0	7,810
28-01-1030	1030	0,002	0,001	852,0	8,320
28-01-1130	1130	0,001	0,001	934,0	8,975
28-01-1240	1240	0,001	0,001	987,0	9,250