

TECHNI PVC 59



Heavy-Duty Absorptive Delivery Hoses

Operating Temperature Range:

-20°C / +65°C (Static Conditions)

-5°C / +43°C (Dynamic Conditions)

Features:

- Can be used for sucking & transmitting.
- Hardened PVC spirals are durable against flexing and breaking

Use for: unloading and sucking of any kind of liquids, water with/without mud and chemicals.

Lengths:

19 mm – 76 mm ID – 50 metres

90 mm – 152 mm ID – 25 metres

203 mm ID – 6 metres

PART CODES: SIZES & TECHNICAL SPECIFICATIONS

PRODUCT CODE	INNER DIAMETER	WORKING PRESSURE	VACUUM	BENDING RADIUS	WEIGHT
	<i>mm</i>	<i>bar</i>	<i>bar</i>	<i>mm</i>	<i>gr./mt.</i>
59-01-19	19	8	900	95	335
59-01-25	25	8	900	125	400
59-01-32	32	7	900	160	580
59-01-38	38	7	900	190	680
59-01-51	51	6	900	250	970
59-01-63	63	5,5	900	315	1405
59-01-76	76	4	900	375	1680
59-01-90	90	4	900	425	2055
59-01-102	102	4	900	500	2600
59-01-127	127	4	900	625	4000
59-01-152	152	4	900	850	5200
59-01-203	203	4	900	1000	8500